## NSN 5306-01-341-6714

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-341-6714

Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

0.469 inches

#### Fastener Length:

Between 2.829 inches and 2.859 inches

#### Head Style:

Hexagon

Head Height:

0.156 inches

#### Width Between Flats:

Between 0.492 inches and 0.564 inches

#### Grip Diameter:

Between 0.3115 inches and 0.3120 inches

### Shank Unthreaded Hole Diameter:

0.076 inches first hole and 0.086 inches first hole

## **Thread Diameter:**

0.312 inches

Grip Length:

Between 2.829 inches and 2.859 inches

### Thready Qty Per Inch (tpi):

24

### Min. Tensile Strength (psi):

160000 pounds per square inch

### Distance From Head Largest Bearing Surface To Shank Hole Center:

2.663 inches first hole

### Surface Finish:

63.0 microinches bearing surface of head63.0 microinches grip16.0 microinches threads

### Material:

Titanium alloy

### **Material Specification:**

Ams4967 assn standard single material response

### **Thread Series Designator:**

Unjf

## Specification Data:

80205-nas675 professional/industrial association standard

#### Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5306-01-341-6714

Shear Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

