
NSN 5306-01-341-8915

Shear Bolt - Page 1 of 2





Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.798 inches

Fastener Length:

Between 1.701 inches and 1.731 inches

Head Style:

Spline extended washer

Head Height:

Between 0.383 inches and 0.403 inches

Extended Washer Diameter:

Between 0.807 inches and 0.817 inches

Extended Washer Thickness:

Between 0.053 inches and 0.073 inches

Grip Diameter:

Between 0.4360 inches and 0.4370 inches

Head Minor Diameter:

Between 0.514 inches and 0.521 inches

Thread Diameter:

0.438 inches

Grip Length:

Between 0.928 inches and 0.948 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

220000 pounds per square inch

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Surface Finish:

32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads

Material:

Steel comp h11

Material Specification:

Ams 6487 assn standard single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Mil-c-8837 type 2, cl 2 military specification single treatment response

Thread Series Designator:

Unjf

NSN 5306-01-341-8915

Shear Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.

