NSN 5306-01-341-8916

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-341-8916

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.674 inches
Fastener Length:
Between 1.721 inches and 1.751 inches
Head Style:
Spline extended washer
Head Height:
Between 0.327 inches and 0.347 inches
Extended Washer Diameter:
Between 0.691 inches and 0.701 inches
Extended Washer Thickness:
Between 0.044 inches and 0.064 inches
Grip Diameter:
Between 0.3736 inches and 0.3746 inches
Head Minor Diameter:
Between 0.448 inches and 0.455 inches
Thread Diameter:
0.375 inches
Grip Length:
Between 1.052 inches and 1.072 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
220000 pounds per square inch
Hardness Rating:
46.0 rockwell c and 50.0 rockwell c
Surface Finish:
32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads
Material:
Steel comp h11
Material Specification:
Ams 6487 assn standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Mil-c-8837 type 2, cl 2 military specification single treatment response

Unjf

Thread Series Designator:

NSN 5306-01-341-8916

Shear Bolt - Page 2 of 2



N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

Shelf Life:

Mil-std (military Standard):

Mil-c-8837 spec.

A003b0