
NSN 5306-01-341-8916

Shear Bolt - Page 1 of 2

Thread Class:





3a **Thread Direction: Right-hand Thread Length:** 0.674 inches Fastener Length: Between 1.721 inches and 1.751 inches **Head Style:** Spline extended washer **Head Height:** Between 0.327 inches and 0.347 inches **Extended Washer Diameter:** Between 0.691 inches and 0.701 inches **Extended Washer Thickness:** Between 0.044 inches and 0.064 inches **Grip Diameter:** Between 0.3736 inches and 0.3746 inches Head Minor Diameter: Between 0.448 inches and 0.455 inches **Thread Diameter:** 0.375 inches Grip Length: Between 1.052 inches and 1.072 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 50.0 rockwell c Surface Finish: 32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Mil-c-8837 type 2, cl 2 military specification single treatment response

Thread Series Designator:

NSN 5306-01-341-8916

Shear Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.

