

View Online at <https://aerobasegroup.com/nsn/5306-01-342-4931>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.377 inches

Fastener Length:

Between 1.611 inches and 1.656 inches

Head Style:

Double hexagon

Head Height:

Between 0.154 inches and 0.174 inches

Width Between Flats:

Between 0.430 inches and 0.439 inches

Grip Diameter:

Between 0.2490 inches and 0.2495 inches

Shank Unthreaded Hole Diameter:

0.071 inches first hole and 0.081 inches first hole

Thread Diameter:

0.250 inches

Grip Length:

Between 1.240 inches and 1.260 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

260000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.459 inches first hole

Material:

Cobalt comp mp-35-n fastener

Material Specification:

Ams 5844 assn standard single material response fastener

Surface Treatment:

Cadmium fastener and chromate fastener

Surface Treatment Specification:

Qq-p-416 type 2, cl 3 federal specification single treatment response fastener

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0