

View Online at <https://aerobasegroup.com/nsn/5306-01-342-4931>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.377 inches

**Fastener Length:**

Between 1.611 inches and 1.656 inches

**Head Style:**

Double hexagon

**Head Height:**

Between 0.154 inches and 0.174 inches

**Width Between Flats:**

Between 0.430 inches and 0.439 inches

**Grip Diameter:**

Between 0.2490 inches and 0.2495 inches

**Shank Unthreaded Hole Diameter:**

0.071 inches first hole and 0.081 inches first hole

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 1.240 inches and 1.260 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

260000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.459 inches first hole

**Material:**

Cobalt comp mp-35-n fastener

**Material Specification:**

Ams 5844 assn standard single material response fastener

**Surface Treatment:**

Cadmium fastener and chromate fastener

**Surface Treatment Specification:**

Qq-p-416 type 2, cl 3 federal specification single treatment response fastener

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0