## NSN 5306-01-342-8551

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-342-8551

| view Offilite at https://aerobasegroup.com/hsh/5500-01-542-0551                       |
|---|
| Thread Class:   |
| 3a  |
| Thread Direction:   |
| Right-hand  |
| Thread Length:  |
| Between 0.680 inches and 0.730 inches   |
| Fastener Length:  |
| Between 1.752 inches and 1.782 inches   |
| Head Style:   |
| Spline extended washer  |
| Head Height:  |
| Between 0.383 inches and 0.403 inches   |
| Extended Washer Diameter:   |
| Between 0.740 inches and 0.750 inches   |
| Extended Washer Thickness:  |
| Between 0.072 inches and 0.092 inches   |
| Grip Diameter:  |
| Between 0.4365 inches and 0.4370 inches   |
| Head Minor Diameter:  |
| Between 0.514 inches and 0.521 inches   |
| Thread Diameter:  |
| 0.437 inches  |
| Grip Length:  |
| Between 1.052 inches and 1.072 inches   |
| Thready Qty Per Inch (tpi):   |
| 20  |
| Min. Tensile Strength (psi):  |
| 180000 pounds per square inch   |
| Surface Finish:   |
| 32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads |
| Material:   |
| Nickel alloy 718  |
| Material Specification:   |
| Ams 5662 assn standard single material response                                       |
| Surface Treatment:  |
| Passivate   |
| Surface Treatment Specification:  |
| Qq-p-35 federal specification single treatment response                               |
| Thread Series Designator:   |
| Unjf  |
| Shelf Life:   |
| N/a   |

## NSN 5306-01-342-8551

Shear Bolt - Page 2 of 2



|   | 1  | :. | ~  | 84  |    |    |      |   |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A003b0