NSN 5306-01-343-1753

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-343-1753

view Online at https://aeiobasegroup.com/nsii/3300-01-343-1733
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
1.009 inches
Fastener Length:
Between 3.681 inches and 3.711 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.701 inches and 0.721 inches
Width Between Flats:
Between 0.803 inches and 0.814 inches
Extended Washer Diameter:
Between 1.220 inches and 1.230 inches
Extended Washer Thickness:
0.178 inches
Grip Diameter:
Between 0.7485 inches and 0.7490 inches
Thread Diameter:
0.750 inches
Grip Length:
Between 2.677 inches and 2.697 inches
Thready Qty Per Inch (tpi):
16
Min. Tensile Strength (psi):
220000 pounds per square inch
Surface Finish:
32.0 microinches bearing surface of head32.0 microinches grip
Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a

NSN 5306-01-343-1753

Shear Bolt - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

