NSN 5306-01-343-2339

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-343-2339

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.718 inches and 0.768 inches
Fastener Length:
Between 2.353 inches and 2.383 inches
Head Style:
Spline extended washer
Head Height:
Between 0.383 inches and 0.403 inches
Extended Washer Diameter:
Between 0.807 inches and 0.817 inches
Extended Washer Thickness:
Between 0.053 inches and 0.073 inches
Grip Diameter:
Between 0.4360 inches and 0.4370 inches
Head Minor Diameter:
Between 0.514 inches and 0.521 inches
Thread Diameter:
0.438 inches
Grip Length:
Between 1.615 inches and 1.635 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
220000 pounds per square inch
Surface Finish:
32.0 microinches grip
Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:

N/a

NSN 5306-01-343-2339

Shear Bolt - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0