

View Online at <https://aerobasegroup.com/nsn/5306-01-343-2346>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

1.175 inches

**Fastener Length:**

Between 4.222 inches and 4.252 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.798 inches and 0.818 inches

**Width Between Flats:**

Between 0.928 inches and 0.940 inches

**Extended Washer Diameter:**

Between 1.428 inches and 1.433 inches

**Extended Washer Thickness:**

0.198 inches

**Grip Diameter:**

Between 0.8735 inches and 0.8740 inches

**Thread Diameter:**

0.875 inches

**Grip Length:**

Between 3.052 inches and 3.072 inches

**Thready Qty Per Inch (tpi):**

14

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Surface Finish:**

32.0 microinches bearing surface of head32.0 microinches grip

**Material:**

Nickel alloy 718

**Material Specification:**

Ams 5662 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0