# NSN 5306-01-343-2762

Shear Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-01-343-2762

### Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

# Thread Length:

Between 0.320 inches and 0.370 inches

#### Fastener Length:

Between 0.892 inches and 0.922 inches

#### Head Style:

Dished hexagon

#### **Head Height:**

Between 0.110 inches and 0.125 inches

#### Width Between Flats:

Between 0.367 inches and 0.376 inches

#### Grip Diameter:

Between 0.1885 inches and 0.1895 inches

**Thread Diameter:** 

0.190 inches

# Grip Length:

Between 0.552 inches and 0.572 inches

## Thready Qty Per Inch (tpi):

32

# Min. Tensile Strength (psi):

160000 pounds per square inch

#### Surface Finish:

32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads

#### Material:

Titanium alloy uns r56400

#### **Material Specification:**

Ams4928 assn standard single material response or ams4967 assn standard single material response

#### Surface Treatment:

Aluminum

#### **Thread Series Designator:**

Unjf

# **Specification Data:**

80205-nas6803 professional/industrial association standard

#### Shelf Life:

N/a

### Unit Of Measure:

--

#### Demilitarization:

No

# NSN 5306-01-343-2762

Shear Bolt - Page 2 of 2

Fiig: A003b0

