

View Online at <https://aerobasegroup.com/nsn/5306-01-343-8809>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.607 inches

Fastener Length:

Between 5.041 inches and 5.081 inches

Head Style:

Hexagon

Head Height:

Between 0.234 inches and 0.266 inches

Width Between Flats:

Between 0.615 inches and 0.627 inches

Shoulder Diameter:

0.433 inches first shoulder and 0.437 inches first shoulder

Shoulder Length:

4.444 inches first shoulder and 4.464 inches first shoulder

Shank Unthreaded Hole Diameter:

0.187 inches first hole and 0.207 inches first hole

Thread Diameter:

0.375 inches

Thready Qty Per Inch (tpi):

24

Distance From Head Largest Bearing Surface To Shank Hole Center:

4.854 inches first hole

Shoulder Shape:

Round first shoulder

Material:

Iron alloy 660

Material Specification:

Ams5731 assn standard single material response or ams5737 assn standard single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 ty2 cl2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0