## NSN 5306-01-344-0610

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-344-0610 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.397 inches **Fastener Length:** Between 1.132 inches and 1.162 inches **Head Style:** Spline extended washer **Head Height:** 0.205 inches **Extended Washer Diameter:** Between 0.349 inches and 0.359 inches **Extended Washer Thickness:** 0.027 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Head Minor Diameter:** Between 0.173 inches and 0.188 inches **Thread Diameter:** 0.190 inches **Grip Length:** 0.750 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 220000 pounds per square inch Surface Finish: 32.0 microinches bearing surface of head32.0 microinches grip Material: Nickel alloy 718 **Material Specification:** Ams5662 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf

Shelf Life: N/a

## NSN 5306-01-344-0610

Shear Bolt - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0