## NSN 5306-01-344-4314

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-344-4314 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.535 inches and 0.585 inches **Fastener Length:** Between 1.045 inches and 1.075 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.378 inches and 0.398 inches Width Between Flats: Between 0.430 inches and 0.439 inches **Extended Washer Diameter:** Between 0.639 inches and 0.649 inches **Extended Washer Thickness:** 0.091 inches **Grip Diameter:** Between 0.3740 inches and 0.3745 inches **Thread Diameter:** 0.375 inches **Grip Length:** Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 220000 pounds per square inch Surface Finish: 32.0 microinches bearing surface of head32.0 microinches grip Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response **Surface Treatment: Passivate** 

**Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** 

Unjf

Shelf Life:

N/a

## NSN 5306-01-344-4314

Shear Bolt - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0