NSN 5306-01-344-5526

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-344-5526 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 1.388 inches **Fastener Length:** Between 2.985 inches and 3.015 inches **Head Style:** Double hexagon w/hole **Head Height:** 0.711 inches Width Between Flats: Between 0.803 inches and 0.814 inches **Extended Washer Diameter:** Between 1.220 inches and 1.230 inches **Extended Washer Thickness:** 0.178 inches **Hole Diameter:** Between 0.410 inches and 0.450 inches First Diameter From Head: Between 0.663 inches and 0.665 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.597 inches and 1.627 inches **End Application:** B₁b **Thread Diameter:** 0.750 inches **Hole Quantity: Hole Type:** Thready Qty Per Inch (tpi): 16 **Hole Configuration Style:** Double hexagon longitudinal hole **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Hole drilled in head-depth 0.331 inch

Material:

Nickel alloy 718

NSN 5306-01-344-5526

Externally Relieved Body Bolt - Page 2 of 2



Material Specificatior	1:
------------------------	----

Ams 5662 assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0