

View Online at <https://aerobasegroup.com/nsn/5306-01-344-8224>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.323 inches

Fastener Length:

Between 1.120 inches and 1.150 inches

Head Style:

Dished hexagon

Head Height:

Between 0.110 inches and 0.125 inches

Width Between Flats:

Between 0.367 inches and 0.376 inches

Grip Diameter:

Between 0.1885 inches and 0.1895 inches

Shank Unthreaded Hole Diameter:

0.070 inches first hole and 0.080 inches first hole

Thread Diameter:

0.190 inches

Grip Length:

Between 0.802 inches and 0.822 inches

Thread Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

120000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.946 inches first hole and 0.996 inches first hole

Surface Finish:

32.0 microinches bearing surface of head 32.0 microinches grip 32.0 microinches threads

Color:

Green threads

Material:

Iron alloy 660

Material Specification:

Ams 5731 assn standard single material response or ams 5737 assn standard single material response

Surface Treatment:

Cadmium fastener and chromate fastener

Surface Treatment Specification:

Qq-p-416 type 2, cl 2 federal specification single treatment response fastener

Thread Series Designator:

Unjf

Specification Data:

80205-nas6303 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0