

View Online at <https://aerobasegroup.com/nsn/5306-01-344-8224>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.323 inches

**Fastener Length:**

Between 1.120 inches and 1.150 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.110 inches and 0.125 inches

**Width Between Flats:**

Between 0.367 inches and 0.376 inches

**Grip Diameter:**

Between 0.1885 inches and 0.1895 inches

**Shank Unthreaded Hole Diameter:**

0.070 inches first hole and 0.080 inches first hole

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 0.802 inches and 0.822 inches

**Thread Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

120000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.946 inches first hole and 0.996 inches first hole

**Surface Finish:**

32.0 microinches bearing surface of head 32.0 microinches grip 32.0 microinches threads

**Color:**

Green threads

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5731 assn standard single material response or ams 5737 assn standard single material response

**Surface Treatment:**

Cadmium fastener and chromate fastener

**Surface Treatment Specification:**

Qq-p-416 type 2, cl 2 federal specification single treatment response fastener

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas6303 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0