NSN 5306-01-345-0568

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-345-0568

Thread Class: За **Thread Direction:** Right-hand Thread Length: Between 1.500 inches and 1.540 inches **Fastener Length:** Between 4.500 inches and 4.530 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 1.041 inches and 1.061 inches Width Between Flats: Between 1.239 inches and 1.252 inches **Extended Washer Diameter:** Between 1.865 inches and 1.875 inches **Extended Washer Thickness:** 0.258 inches **Grip Diameter:** Between 1.1235 inches and 1.1240 inches **Thread Diameter:** 1.125 inches **Grip Length:** Between 2.990 inches and 3.010 inches Thready Qty Per Inch (tpi): 12 Min. Tensile Strength (psi): 220000 pounds per square inch Surface Finish: 32.0 microinches bearing surface of head32.0 microinches grip Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5306-01-345-0568

Shear Bolt - Page 2 of 2



| | Of | | | |
|--|----|--|--|--|

--

Demilitarization:

No

Fiig:

A003b0