

View Online at <https://aerobasegroup.com/nsn/5306-01-345-2430>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.461 inches and 0.471 inches

**Fastener Length:**

Between 4.170 inches and 4.190 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.365 inches and 0.385 inches

**Width Between Flats:**

0.419 inches

**Extended Washer Diameter:**

Between 0.490 inches and 0.510 inches

**Extended Washer Thickness:**

Between 0.070 inches and 0.080 inches

**Shoulder Diameter:**

0.309 inches all shoulders and 0.311 inches all shoulders

**Shoulder Length:**

0.770 inches first shoulder and 0.830 inches first shoulder 0.809 inches second shoulder and 0.859 inches second shoulder

**Hole Diameter:**

Between 0.196 inches and 0.216 inches

**End Application:**

Pacer dawn

**Thread Diameter:**

0.250 inches

**Hole Quantity:**

1

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

28

**Hole Configuration Style:**

Double hexagon longitudinal hole

**Shoulder Shape:**

Round first shoulder round second shoulder

**Special Features:**

Distance between both shoulders is 2.080 inches: used on tfe-1042

**Material:**

Iron alloy 660

**Material Specification:**

Ams 7477 assn standard single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0