

View Online at <https://aerobasegroup.com/nsn/5306-01-345-3739>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.516 inches

Fastener Length:

3.215 inches

Head Style:

Round w/wrench flats

Head Diameter:

0.875 inches

Head Height:

0.250 inches

Width Between Flats:

0.750 inches

Shoulder Diameter:

0.498 inches first shoulder and 0.499 inches first shoulder

Shoulder Length:

3.215 inches first shoulder

Shank Unthreaded Hole Diameter:

0.106 inches first hole and 0.116 inches first hole

Thread Diameter:

0.375 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

200000 pounds per square inch

Hardness Rating:

43.0 rockwell c and 48.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

3.486 inches first hole

Shoulder Shape:

Round first shoulder

Product Name:

Navy special project

Material:

Stainless steel

Material Specification:

Mil-s-5002 military specification single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5002 spec.