

View Online at <https://aerobasegroup.com/nsn/5306-01-345-6687>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.503 inches and 0.553 inches

Fastener Length:

Between 2.451 inches and 2.481 inches

Head Style:

Dished hexagon

Head Height:

Between 0.219 inches and 0.234 inches

Width Between Flats:

Between 0.678 inches and 0.690 inches

Grip Diameter:

Between 0.4365 inches and 0.4370 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole and 0.116 inches first hole

Thread Diameter:

0.438 inches

Grip Length:

Between 1.928 inches and 1.948 inches

Thread Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

160000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.242 inches first hole and 2.292 inches first hole

Surface Finish:

32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads

Material:

Iron alloy 660

Material Specification:

Ams 5731 assn standard single material response or ams 5737 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas6307 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0