NSN 5306-01-345-9526

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-345-9526 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.868 inches **Fastener Length:** Between 5.603 inches and 5.633 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.608 inches and 0.628 inches Width Between Flats: Between 0.679 inches and 0.690 inches **Extended Washer Diameter:** Between 1.040 inches and 1.050 inches **Extended Washer Thickness:** 0.150 inches **Grip Diameter:** Between 0.6235 inches and 0.6240 inches **Thread Diameter:** 0.625 inches **Grip Length:** Between 4.740 inches and 4.760 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 220000 pounds per square inch Surface Finish: 32.0 microinches bearing surface of head32.0 microinches grip Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf

N/a

Shelf Life:

NSN 5306-01-345-9526

Shear Bolt - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A003b0