

View Online at <https://aerobasegroup.com/nsn/5306-01-346-1030>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.388 inches and 0.448 inches

**Fastener Length:**

Between 1.930 inches and 1.990 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

0.338 inches

**Width Between Flats:**

0.420 inches

**Extended Washer Diameter:**

0.500 inches

**Extended Washer Thickness:**

0.070 inches

**Hole Diameter:**

Between 0.076 inches and 0.086 inches

**Shank Unthreaded Hole Diameter:**

0.011 inches all holes and 0.017 inches all holes

**End Application:**

Pacer dawn

**Thread Diameter:**

0.313 inches

**Hole Quantity:**

1

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

24

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.820 inches first hole

**Special Features:**

Altered item drawing - make from ms9725-26: next assembly 3092400: used on tfe1042-70

**Material:**

Copper alloy

**Material Specification:**

Ams 5708 assn standard single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0