NSN 5306-01-346-1030

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-346-1030

| 3 |
|---|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.388 inches and 0.448 inches |
| Fastener Length: |
| Between 1.930 inches and 1.990 inches |
| Head Style: |
| Double hexagon w/hole |
| Head Height: |
| 0.338 inches |
| Width Between Flats: |
| 0.420 inches |
| Extended Washer Diameter: |
| 0.500 inches |
| Extended Washer Thickness: |
| 0.070 inches |
| Hole Diameter: |
| Between 0.076 inches and 0.086 inches |
| Shank Unthreaded Hole Diameter: |
| 0.011 inches all holes and 0.017 inches all holes |
| End Application: |
| Pacer dawn |
| Thread Diameter: |
| 0.313 inches |
| Hole Quantity: |
| 1 |
| Hole Type: |
| Drilled |
| Thready Qty Per Inch (tpi): |
| 24 |
| Distance From Head Largest Bearing Surface To Shank Hole Center: |
| 1.820 inches first hole |
| Special Features: |
| Altered item drawing - make from ms9725-26: next assembly 3092400: used on tfe1042-70 |
| Material: |
| Copper alloy |
| Material Specification: |
| Ams 5708 assn standard single material response |
| Thread Series Designator: |
| Unjf |

NSN 5306-01-346-1030

Machine Bolt - Page 2 of 2



| | | ife: | |
|--|--|------|--|
| | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0