

View Online at <https://aerobasegroup.com/nsn/5306-01-346-1031>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.323 inches

Fastener Length:

Between 0.808 inches and 0.838 inches

Head Style:

Hexagon

Head Height:

Between 0.110 inches and 0.125 inches

Width Between Flats:

Between 0.367 inches and 0.376 inches

Grip Diameter:

Between 0.191 inches and 0.192 inches

Shank Unthreaded Hole Diameter:

0.070 inches first hole and 0.080 inches first hole

End Application:

Pacer dawn

Thread Diameter:

0.190 inches

Grip Length:

Between 0.490 inches and 0.510 inches

Thready Qty Per Inch (tpi):

32

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.664 inches first hole

Special Features:

Altered item drawing-make from nas6303u8d: hole diameter 0.070/0.080: next assembly 3092400: used on tfe1042-70

Material:

Iron alloy 660

Material Specification:

Ams 5731 assn standard single material response

Surface Treatment:

Nickel head

Surface Treatment Specification:

Ams 2433 assn standard single treatment response head

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0