

View Online at <https://aerobasegroup.com/nsn/5306-01-346-2260>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.523 inches and 0.553 inches

Fastener Length:

Between 5.135 inches and 5.543 inches

Head Style:

Hexagon

Head Height:

Between 0.250 inches and 0.265 inches

Width Between Flats:

Between 0.741 inches and 0.752 inches

Grip Diameter:

Between 0.4990 inches and 0.4995 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole and 0.116 inches first hole

Thread Diameter:

0.500 inches

Grip Length:

Between 5.346 inches and 5.355 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

160000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

5.346 inches first hole and 5.355 inches first hole

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

Thread Series Designator:

Unjf

Specification Data:

80205-nas6408 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0