NSN 5306-01-346-2388

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-346-2388 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.601 inches and 0.651 inches **Fastener Length:** Between 2.236 inches and 2.266 inches **Head Style:** Dished hexagon **Head Height:** Between 0.312 inches and 0.327 inches Width Between Flats: Between 0.928 inches and 0.940 inches **Grip Diameter:** Between 0.6230 inches and 0.6240 inches **Thread Diameter:** 0.625 inches **Grip Length:** Between 1.615 inches and 1.635 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 160000 pounds per square inch **Surface Finish:** 32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Aluminum **Thread Series Designator:** Unjf **Specification Data:** 80205-nas6410 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5306-01-346-2388

Shear Bolt - Page 2 of 2



Fiig:

A003b0