## NSN 5306-01-346-2390

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-346-2390 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.641 inches and 0.691 inches **Fastener Length:** Between 2.589 inches and 2.619 inches **Head Style:** Dished hexagon **Head Height:** Between 0.375 inches and 0.390 inches Width Between Flats: Between 1.052 inches and 1.065 inches **Grip Diameter:** Between 0.7480 inches and 0.7490 inches **Thread Diameter:** 0.750 inches **Grip Length:** Between 1.928 inches and 1.948 inches Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 160000 pounds per square inch **Surface Finish:** 32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Aluminum **Thread Series Designator:** Unjf **Specification Data:** 80205-nas6412 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5306-01-346-2390

Shear Bolt - Page 2 of 2



Fiig:

A003b0