## NSN 5306-01-346-3682



Shear Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-346-3682 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.438 inches **Fastener Length:** Between 0.735 inches and 0.765 inches **Head Style:** Dished hexagon **Head Height:** Between 0.156 inches and 0.171 inches Width Between Flats: Between 0.492 inches and 0.502 inches **Grip Diameter:** Between 0.3115 inches and 0.3120 inches **Shank Unthreaded Hole Diameter:** 0.076 inches first hole and 0.086 inches first hole **Thread Diameter:** 0.312 inches **Grip Length:** Between 0.365 inches and 0.385 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 0.568 inches first hole Material: Titanium alloy uns r56400 **Material Specification:** 

0.568 inches first hole

Material:

Titanium alloy uns r56400

Material Specification:

Ams4967 assn standard single material response or ams4928 assn standard single material response

Thread Series Designator:

Unjf

Specification Data:

80205-nas6405 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

## NSN 5306-01-346-3682

Shear Bolt - Page 2 of 2



Fiig:

A003b0