## NSN 5306-01-346-3682

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-346-3682

View Online at https://aerobasegroup.com/nsn/5306-01-346-3682
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
0.438 inches
Fastener Length:
Between 0.735 inches and 0.765 inches
Head Style:
Dished hexagon
Head Height:
Between 0.156 inches and 0.171 inches
Width Between Flats:
Between 0.492 inches and 0.502 inches
Grip Diameter:
Between 0.3115 inches and 0.3120 inches
Shank Unthreaded Hole Diameter:
0.076 inches first hole and 0.086 inches first hole
Thread Diameter:
0.312 inches
Grip Length:
Between 0.365 inches and 0.385 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Distance From Head Largest Bearing Surface To Shank Hole Center:
0.568 inches first hole
Material:
Titanium alloy uns r56400
Material Specification:
Ams4967 assn standard single material response or ams4928 assn standard single material response
Thread Series Designator:
Unjf
Specification Data:
80205-nas6405 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

## NSN 5306-01-346-3682

Shear Bolt - Page 2 of 2

Fiig: A003b0

