## NSN 5306-01-346-5299

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-346-5299

Thread	Class
meau	<b>UIASS</b> .

3a

**Thread Direction:** 

**Right-hand** 

### Thread Length:

0.469 inches

#### Fastener Length:

Between 2.392 inches and 2.422 inches

#### Head Style:

Hexagon

Head Height:

Between 0.156 inches and 0.171 inches

#### Width Between Flats:

Between 0.492 inches and 0.502 inches

#### Grip Diameter:

Between 0.3110 inches and 0.3120 inches

#### **Thread Diameter:**

0.312 inches

## Grip Length:

Between 1.928 inches and 1.948 inches

#### Thready Qty Per Inch (tpi):

24

#### Min. Tensile Strength (psi):

160000 pounds per square inch

Material:

Iron alloy 660

#### **Material Specification:**

Ams 5731 assn standard single material response or ams 5737 assn standard single material response

#### Surface Treatment:

Cadmium and chromate

#### Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

#### **Thread Series Designator:**

Unjf

#### **Specification Data:**

80205-nas6705 professional/industrial association standard

#### Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

# NSN 5306-01-346-5299

Shear Bolt - Page 2 of 2

Fiig: A003b0

