## NSN 5306-01-347-0236

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-347-0236 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.877 inches and 0.927 inches **Fastener Length:** Between 2.575 inches and 2.605 inches **Head Style:** Dished hexagon **Head Height:** Between 0.312 inches and 0.327 inches Width Between Flats: Between 0.928 inches and 0.940 inches **Hole Diameter:** 0.070 inches **Grip Diameter:** Between 0.6230 inches and 0.6240 inches **Shank Unthreaded Hole Diameter:** 0.141 inches first hole **Thread Diameter:** 0.625 inches **Grip Length:** Between 1.678 inches and 1.698 inches **Hole Quantity:** 3 **Hole Type:** Drilled Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 180000 pounds per square inch **Hole Configuration Style:** Hexagon corners Distance From Head Largest Bearing Surface To Shank Hole Center: 1.716 inches first hole Material: Iron alloy 660 **Surface Treatment: Passivate** 

Thread S

**Thread Series Designator:** 

Unjf

## NSN 5306-01-347-0236

Shear Bolt - Page 2 of 2



_				-		
C	h	Δ	Iŧ.		ife:	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0