NSN 5306-01-347-2002

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-347-2002 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.500 inches and 0.520 inches **Fastener Length:** Between 1.552 inches and 1.572 inches **Head Style:** Double hexagon extended washer **Head Height:** Between 0.365 inches and 0.385 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Extended Washer Diameter:** Between 0.490 inches and 0.510 inches **Extended Washer Thickness:** Between 0.070 inches and 0.080 inches **First Diameter From Head:** Between 0.235 inches and 0.240 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.852 inches and 0.872 inches **End Application:** Pacer dawn **Thread Diameter:** 0.313 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity: Special Features:** Used on tfe1042 Material: Nickel alloy 718 **Material Specification:** Ams 5663 inco 718 assn standard single material response **Thread Series Designator:** Unf Shelf Life: N/a

Unit Of Measure:

NSN 5306-01-347-2002

Externally Relieved Body Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0