NSN 5306-01-347-2004

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-347-2004

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.578 inches
Fastener Length:
Between 1.625 inches and 1.655 inches
Head Style:
Dished hexagon
Head Height:
Between 0.188 inches and 0.203 inches
Width Between Flats:
Between 0.554 inches and 0.564 inches
Grip Diameter:
Between 0.3735 inches and 0.3745 inches
Shank Unthreaded Hole Diameter:
0.106 inches first hole and 0.116 inches first hole
Thread Diameter:
0.375 inches
Grip Length:
Between 1.052 inches and 1.072 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Distance From Head Largest Bearing Surface To Shank Hole Center:
1.443 inches first hole
Material:
Titanium alloy uns r56400
Material Specification:
Ams4928 assn standard single material response or ams4967 assn standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 ty2 cl2 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas6806 professional/industrial association standard
Shelf Life:
N/a

NSN 5306-01-347-2004

Shear Bolt - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

