## NSN 5306-01-347-2008

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-347-2008

Thread Class:  3a Thread Direction: Right-hand Thread Length: 0.323 inches Fastener Length: Between 1.370 inches and 1.400 inches Head Style: Hexagon Head Height: Between 0.110 inches and 0.125 inches Width Between Flats: Between 0.367 inches and 0.376 inches Hole Diameter: Between 0.046 inches and 0.056 inches
Thread Direction: Right-hand Thread Length: 0.323 inches Fastener Length: Between 1.370 inches and 1.400 inches Head Style: Hexagon Head Height: Between 0.110 inches and 0.125 inches Width Between Flats: Between 0.367 inches and 0.376 inches Hole Diameter: Between 0.046 inches and 0.056 inches
Right-hand Thread Length: 0.323 inches Fastener Length: Between 1.370 inches and 1.400 inches Head Style: Hexagon Head Height: Between 0.110 inches and 0.125 inches Width Between Flats: Between 0.367 inches and 0.376 inches Hole Diameter: Between 0.046 inches and 0.056 inches
Thread Length:  0.323 inches  Fastener Length:  Between 1.370 inches and 1.400 inches  Head Style:  Hexagon  Head Height:  Between 0.110 inches and 0.125 inches  Width Between Flats:  Between 0.367 inches and 0.376 inches  Hole Diameter:  Between 0.046 inches and 0.056 inches
0.323 inches  Fastener Length: Between 1.370 inches and 1.400 inches  Head Style: Hexagon Head Height: Between 0.110 inches and 0.125 inches  Width Between Flats: Between 0.367 inches and 0.376 inches  Hole Diameter: Between 0.046 inches and 0.056 inches
Fastener Length: Between 1.370 inches and 1.400 inches  Head Style: Hexagon  Head Height: Between 0.110 inches and 0.125 inches  Width Between Flats: Between 0.367 inches and 0.376 inches  Hole Diameter: Between 0.046 inches and 0.056 inches
Between 1.370 inches and 1.400 inches  Head Style: Hexagon  Head Height: Between 0.110 inches and 0.125 inches  Width Between Flats: Between 0.367 inches and 0.376 inches  Hole Diameter: Between 0.046 inches and 0.056 inches
Head Style: Hexagon Head Height: Between 0.110 inches and 0.125 inches Width Between Flats: Between 0.367 inches and 0.376 inches Hole Diameter: Between 0.046 inches and 0.056 inches
Hexagon  Head Height:  Between 0.110 inches and 0.125 inches  Width Between Flats:  Between 0.367 inches and 0.376 inches  Hole Diameter:  Between 0.046 inches and 0.056 inches
Head Height:  Between 0.110 inches and 0.125 inches  Width Between Flats:  Between 0.367 inches and 0.376 inches  Hole Diameter:  Between 0.046 inches and 0.056 inches
Between 0.110 inches and 0.125 inches  Width Between Flats:  Between 0.367 inches and 0.376 inches  Hole Diameter:  Between 0.046 inches and 0.056 inches
Width Between Flats:  Between 0.367 inches and 0.376 inches  Hole Diameter:  Between 0.046 inches and 0.056 inches
Between 0.367 inches and 0.376 inches  Hole Diameter:  Between 0.046 inches and 0.056 inches
Hole Diameter: Between 0.046 inches and 0.056 inches
Between 0.046 inches and 0.056 inches
O. C. Diversity
Grip Diameter:
Between 0.1885 inches and 0.1895 inches
Thread Diameter:
0.190 inches
Grip Length:
Between 1.052 inches and 1.072 inches
Hole Quantity:
3
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Hole Configuration Style:
Hexagon corners
Surface Finish:
32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads
Material:
Steel comp e4340 or steel comp 8740
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

## NSN 5306-01-347-2008

Shear Bolt - Page 2 of 2

A003b0



Thread Series Designator:
Unjf
Specification Data:
80205-nas6210 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: