

View Online at <https://aerobasegroup.com/nsn/5306-01-348-0794>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.370 inches

**Fastener Length:**

Between 1.615 inches and 1.635 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.126 inches and 0.141 inches

**Width Between Flats:**

Between 0.430 inches and 0.439 inches

**Grip Diameter:**

Between 0.2487 inches and 0.2492 inches

**Shank Unthreaded Hole Diameter:**

0.076 inches first hole and 0.086 inches first hole

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 1.125 inches and 1.135 inches

**Thready Qty Per Inch (tpi):**

28

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.500 inches first shoulder

**Special Features:**

Ball, cres qq-s-763, type 440c; plunger and pawl, steel ams 5629ger and pawl,

**Material:**

Stainless steel spring or cobalt alloy spring

**Material Specification:**

Ams 5662 assn standard single material response fastener

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0