

View Online at <https://aerobasegroup.com/nsn/5306-01-348-2652>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.429 inches and 0.449 inches

**Fastener Length:**

3.750 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

0.308 inches

**Head Height:**

0.185 inches

**First Diameter From Head:**

Between 0.164 inches and 0.169 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

3.311 inches

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.190 inches

**Width Across Flats:**

Between 0.1562 inches and 0.1587 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

140000 pounds per square inch

**Externally Relieved Body Diameter Quantity:**

1

**Special Features:**

Apply mil-I-8937 to threads, shank and underside of head; remainder of head and internal drive to be lube free

**Material:**

Iron alloy 660

**Material Specification:**

Ams5731 assn standard single material response or ams5737 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0