NSN 5306-01-348-2668

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-348-2668 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.500 inches **Fastener Length:** Between 1.365 inches and 1.385 inches **Head Style:** Hexagon **Head Height:** Between 0.126 inches and 0.141 inches Width Between Flats: Between 0.430 inches and 0.438 inches **Grip Diameter:** Between 0.2487 inches and 0.2492 inches **Shank Unthreaded Hole Diameter:** 0.076 inches first hole and 0.086 inches first hole **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.865 inches and 0.885 inches Thready Qty Per Inch (tpi): 28 Distance From Head Largest Bearing Surface To Shank Hole Center: 1.250 inches first hole **Special Features:** Furnished with castellated nut retaining element; retaining element shall be released only by depressing plunger located in thread end of bolt Material: Nickel alloy 718 **Material Specification:** Ams5662 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf

N/a

Shelf Life:

Unit Of Measure:

NSN 5306-01-348-2668

Close Tolerance Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0