## NSN 5306-01-348-6014

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-348-6014

Thread	Class:

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

0.538 inches

#### Fastener Length:

Between 1.273 inches and 1.303 inches

#### Head Style:

Spline extended washer

#### Head Height:

Between 0.302 inches and 0.322 inches

#### **Extended Washer Diameter:**

Between 0.575 inches and 0.585 inches

#### **Extended Washer Thickness:**

Between 0.035 inches and 0.055 inches

#### **Grip Diameter:**

Between 0.3110 inches and 0.3120 inches

#### Head Minor Diameter:

0.383 inches

## Thread Diameter:

0.312 inches

#### Grip Length:

Between 0.740 inches and 0.760 inches

#### Thready Qty Per Inch (tpi):

24

#### Min. Tensile Strength (psi):

220000 pounds per square inch

#### Surface Finish:

32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads

#### Material:

Nickel alloy 718

#### Material Specification:

Ams 5662 assn standard single material response

#### Surface Treatment:

Cadmium and chromate

## Surface Treatment Specification:

Qq-p-416 ty2, cl2 federal specification single treatment response

## Thread Series Designator:

Unjf

#### Shelf Life:

N/a

# NSN 5306-01-348-6014

Shear Bolt - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

