NSN 5306-01-348-7085

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-348-7085 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.429 inches and 0.479 inches **Fastener Length:** Between 1.189 inches and 1.219 inches **Head Style:** Dished hexagon **Head Height:** Between 0.188 inches and 0.203 inches Width Between Flats: Between 0.554 inches and 0.564 inches **Locking Feature:** Strip threads or patch threads or pellet threads **Grip Diameter:** Between 0.1740 inches and 0.1745 inches **Thread Diameter:** 0.375 inches **Grip Length:** Between 0.740 inches and 0.760 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Surface Finish:** 32.0 microinches bearing surface of head32.0 microinches threads Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas6406 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5306-01-348-7085

Shear Bolt - Page 2 of 2



Fiig:

A003b0