

View Online at <https://aerobasegroup.com/nsn/5306-01-348-8454>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.583 inches

**Fastener Length:**

Between 1.629 inches and 1.676 inches

**Head Style:**

Double hexagon

**Head Height:**

Between 0.247 inches and 0.267 inches

**Width Between Flats:**

Between 0.678 inches and 0.689 inches

**Grip Diameter:**

Between 0.4365 inches and 0.4370 inches

**Shank Unthreaded Hole Diameter:**

0.101 inches first hole and 0.111 inches first hole

**Thread Diameter:**

0.437 inches

**Grip Length:**

1.062 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.030 inches first hole

**Surface Finish:**

32.0 microinches grip

**Product Name:**

Navy special project

**Material:**

Nickel alloy 718

**Material Specification:**

Ams 5662 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0