

View Online at <https://aerobasegroup.com/nsn/5306-01-349-0801>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

1.047 inches

**Fastener Length:**

Between 4.156 inches and 4.203 inches

**Head Style:**

Double hexagon

**Head Height:**

Between 0.458 inches and 0.478 inches

**Width Between Flats:**

Between 1.239 inches and 1.252 inches

**Grip Diameter:**

Between 0.8735 inches and 0.8740 inches

**Shank Unthreaded Hole Diameter:**

0.136 inches first hole and 0.146 inches first hole

**Thread Diameter:**

0.875 inches

**Grip Length:**

3.125 inches

**Thready Qty Per Inch (tpi):**

14

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

3.934 inches first hole

**Surface Finish:**

32.0 microinches grip

**Product Name:**

Navy special project

**Material:**

Nickel alloy 718

**Material Specification:**

Ams 5662 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0