

View Online at <https://aerobasegroup.com/nsn/5306-01-349-0809>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.914 inches

Fastener Length:

Between 2.586 inches and 2.616 inches

Head Style:

Spline drive shear head

Head Height:

Between 0.390 inches and 0.410 inches

Grip Diameter:

Between 0.7480 inches and 0.7490 inches

Shank Unthreaded Hole Diameter:

0.141 inches first hole and 0.146 inches first hole

Head Minor Diameter:

1.096 inches

Thread Diameter:

0.750 inches

Grip Length:

Between 1.677 inches and 1.697 inches

Thread Qty Per Inch (tpi):

16

Min. Tensile Strength (psi):

125000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.458 inches first hole and 2.478 inches first hole

Material:

Nickel alloy 718

Material Specification:

Ams 5662 assn standard single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0