

View Online at <https://aerobasegroup.com/nsn/5306-01-349-0811>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.599 inches

**Fastener Length:**

Between 1.609 inches and 1.639 inches

**Head Style:**

Spline drive shear head

**Head Height:**

Between 0.247 inches and 0.267 inches

**Grip Diameter:**

Between 0.4360 inches and 0.4370 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole and 0.111 inches first hole

**Head Minor Diameter:**

0.708 inches

**End Application:**

Support equipment (se), b-2 bomber; aircraft, b-2 bomber (atb)

**Thread Diameter:**

0.437 inches

**Grip Length:**

Between 1.115 inches and 1.135 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.491 inches first hole and 1.511 inches first hole

**Material:**

Nickel alloy 718

**Material Specification:**

Ams 5662 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0