

View Online at <https://aerobasegroup.com/nsn/5306-01-349-0811>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.599 inches

Fastener Length:

Between 1.609 inches and 1.639 inches

Head Style:

Spline drive shear head

Head Height:

Between 0.247 inches and 0.267 inches

Grip Diameter:

Between 0.4360 inches and 0.4370 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole and 0.111 inches first hole

Head Minor Diameter:

0.708 inches

End Application:

Support equipment (se), b-2 bomber; aircraft, b-2 bomber (atb)

Thread Diameter:

0.437 inches

Grip Length:

Between 1.115 inches and 1.135 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

125000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.491 inches first hole and 1.511 inches first hole

Material:

Nickel alloy 718

Material Specification:

Ams 5662 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0