## NSN 5306-01-349-4182

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-349-4182

9 F
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.665 inches
Fastener Length:
Between 2.025 inches and 2.055 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.425 inches and 0.445 inches
Width Between Flats:
Between 0.492 inches and 0.502 inches
Extended Washer Diameter:
Between 0.740 inches and 0.750 inches
Extended Washer Thickness:
Between 0.089 inches and 0.109 inches
Hole Diameter:
Between 0.050 inches and 0.060 inches
Grip Diameter:
Between 0.4365 inches and 0.4370 inches
Thread Diameter:
0.437 inches
Grip Length:
Between 1.365 inches and 1.385 inches
Hole Quantity:
1
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
220000 pounds per square inch
Hole Configuration Style:
Double hexagon longitudinal hole
Surface Finish:
32.0 microinches bearing surface of head32.0 microinches grip
Product Name:
Navy special project
Material:
Nickel alloy 718

## NSN 5306-01-349-4182

Shear Bolt - Page 2 of 2

Fiig: A003b0



Material Specification:
Ams 5662 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No