## NSN 5306-01-349-4183

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-349-4183

Thread Oliver
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.828 inches
Fastener Length:
Between 2.375 inches and 2.405 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.547 inches and 0.567 inches
Width Between Flats:
Between 0.616 inches and 0.627 inches
Extended Washer Diameter:
Between 0.928 inches and 0.938 inches
Extended Washer Thickness:
Between 0.123 inches and 0.143 inches
Grip Diameter:
Between 0.5610 inches and 0.5615 inches
Thread Diameter:
0.562 inches
Grip Length:
Between 1.552 inches and 1.572 inches
Thready Qty Per Inch (tpi):
18
Min. Tensile Strength (psi):
220000 pounds per square inch
Surface Finish:
32.0 microinches bearing surface of head32.0 microinches grip
Product Name:
Navy special project
Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:

Unjf

## NSN 5306-01-349-4183

Shear Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

