

View Online at <https://aerobasegroup.com/nsn/5306-01-349-5127>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.429 inches and 0.478 inches

Fastener Length:

Between 1.627 inches and 1.657 inches

Head Style:

Dished hexagon

Head Height:

Between 0.173 inches and 0.193 inches

Width Between Flats:

Between 0.554 inches and 0.564 inches

Grip Diameter:

Between 0.3740 inches and 0.3745 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole and 0.116 inches first hole

Thread Diameter:

0.375 inches

Grip Length:

Between 1.179 inches and 1.198 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.434 inches first hole and 1.484 inches first hole

Material:

Titanium alloy uns r56400

Material Specification:

Ams4928 assn standard single material response or ams4967 assn standard single material response

Thread Series Designator:

Unjf

Specification Data:

80205-nas6406 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0