NSN 5306-01-349-9552

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-349-9552 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.908 inches **Fastener Length:** Between 2.329 inches and 2.359 inches **Head Style:** Spline extended washer **Head Height:** Between 0.440 inches and 0.460 inches **Extended Washer Diameter:** Between 0.922 inches and 0.932 inches **Extended Washer Thickness:** Between 0.062 inches and 0.082 inches **Grip Diameter:** Between 0.4985 inches and 0.4995 inches **Head Minor Diameter:** Between 0.547 inches and 0.562 inches **Thread Diameter:** 0.500 inches **Grip Length:** Between 1.615 inches and 1.635 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch Surface Finish: 32.0 microinches bearing surface of head32.0 microinches grip Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf

Shelf Life:

N/a

NSN 5306-01-349-9552

Shear Bolt - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0