

View Online at <https://aerobasegroup.com/nsn/5306-01-350-0642>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.345 inches and 0.395 inches

Fastener Length:

Between 0.793 inches and 0.823 inches

Head Style:

Dished hexagon

Head Height:

Between 0.125 inches and 0.140 inches

Width Between Flats:

Between 0.429 inches and 0.439 inches

Locking Feature:

Patch threads or pellet threads or strip threads

Grip Diameter:

Between 0.2490 inches and 0.2495 inches

Thread Diameter:

0.250 inches

Grip Length:

Between 0.428 inches and 0.448 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

160000 pounds per square inch

Surface Finish:

32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads

Material:

Plastic polyamide locking featuretitanium alloy uns r56400 fastener

Material Specification:

Ams 4928 assn standard single material response fastener or ams 4967 assn standard single material response fastener

Thread Series Designator:

Unjf

Specification Data:

80205-nas6404 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0